

# **Crossover to flexible efficiency**

#### HardHat® canopy

The HardHat® protects all internal components, keeps the machine looking as good as "new" and increases the residual value.

# Easy to move

Lightweight and compact, these models can be easily towed. Mounted on a single axle, these compressors are easy to manouver on site.

#### Fuel efficiency

Combining the Atlas Copco screw element with a Kubota diesel engine, we deliver a compressor that is best in class in terms of fuel economy.

### Service efficiency

The long service intervals and longer life of all consumables reduce operational costs and increase utilization. Spin-on filters and a spin-on oil separator element means you can change all consumables in minutes.

## Spillage free frame

110% guaranteed to contain all fluids. This is not an option – it comes as standard. The 3 layer corrosion protection coating (category C3) extends lifetime and increases residual value.



Model		XAS 138	<b>XAHS 108</b>
Performance			
Nominal effective working pressure	bar (g)	7	12
	psi (g)	100	175
Free air delivery	cfm	241	186
	m³/min	7	5
	l/sec	114	88
Max. ambient temp. at sea level	°C	50	
Min. starting temperature	°C	-10	
Min. starting temp. (cold start)	°C	-20	
Engine			
Engine Brand	-	Kubota	
Engine Model	-	V2403-M-DI-T-E2B	
Emission level	-	Stage II	
Number of cylinder	-	4	
Engine power	kW	49.2	
Full load	rpm	2700	
Unload	rpm	1600	
Capacity			
Engine oil	I	11.5	
Compressor oil	I	11	
Fuel tank	1	87	
Noise level			
Sound pressure level (LpA) at 7m	dB(A)	72	
Dimensions			
lenght (inc fixed towbar)	mm	3747	
width	mm	1593	
height	mm	1572	
weight	kg	130	0



